



www.mrcoolversapro.com

VersaPro™ 96% AFUE GAS FURNACE MGM96EE****NB



- ✓ Quiet Operation
- ✓ Superior Performance
- ✓ Durable Build & Finish
- ✓ Optional LP Kit
- ✓ Multi-Position Application
- ✓ 96% AFUE
- ✓ Two Stage
- ✓ Energy Efficient
- ✓ Compact Design

(904) 424-9773

Version Date:07-30-2024



VersaPro™ 96% AFUE GAS FURNACE

MGM96EE**NB**

Facing even the most severe winter conditions, the MRCOOL® VersaPro™ 96% AFUE Gas Furnace delivers unparalleled performance with its quiet operation and high efficiency.

Its two-stage, consistent torque DC motor and 96% AFUE ensure significant savings on utility bills. Crafted with an aluminized steel tubular heat exchanger and stainless steel secondary heat exchanger, it guarantees durability and reliability.

Installation is hassle-free, fitting even in areas with limited space. Designed for multi-position installation in upflow or horizontal configurations, the furnace offers convenient left or right connections for gas or electric service. The inclusion of a removable bottom panel facilitates maintenance and installation, accommodating side or bottom return applications. Additionally, conversion to propane is straightforward with an optional LP kit.

The furnace's AHRI certification and ETL listing attest to its adherence to rigorous quality and performance standards. Registering the furnace within 90 days activates a 10-year parts warranty and a lifetime warranty on the heat exchanger, providing additional peace of mind. Even without registration, you're covered by a 5-year parts warranty and a 20-year heat exchanger warranty, ensuring enduring comfort and reliability.

For More Information or Purchase Call (904) 424-9773

SPECIFICATION

GAS FURNACE - 96% AFUE

| UPFLOW HORIZONTAL | Unit | MGM96EE060B3NB | MGM96EE080B3NB | MGM96EE080C4NB | MGM96EE100C5NB | MGM96EE120D5NB | |
|----------------------|---------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|---------|
| Power Supply | V~Hz,Ph | 120~60, 1 | 120~60, 1 | 120~60, 1 | 120~60, 1 | 120~60, 1 | |
| Natural Gas | Input | Btu/h | 60,000 | 80,000 | 80,000 | 100,000 | 120,000 |
| | Output | Btu/h | 57,000 | 76,000 | 76,000 | 95,000 | 115,000 |
| Blower Size | inch | 12.375 x 8 | 12.375 x 8 | 12.75 x 11.25 | 12.75 x 11.25 | 12.75 x 11.25 | |
| Temp. Rise Range | °F | 30-60 | 35-65 | 35-65 | 35-65 | 40-70 | |
| Cabinet Size (WxDxH) | inch | 17.52 x 28.74 x 33.74 | 17.52 x 28.74 x 33.74 | 20.98 x 28.74 x 33.74 | 20.98 x 28.74 x 33.74 | 24.49 x 28.74 x 33.74 | |
| Packing Size (WxDxH) | inch | 20 x 31.02 x 40.35 | 20 x 31.02 x 40.35 | 23.54 x 31.02 x 40.35 | 23.54 x 31.02 x 40.35 | 27.05 x 31.02 x 40.35 | |
| Motor | HP | 3/4 | 3/4 | 3/4 | 1 | 1 | |
| Max CFM @ 0.5ESP | CFM | 1280 | 1271 | 1312 | 2031 | 2127 | |
| Motor Speeds | | 5 speed | 5 speed | 5 speed | 5 speed | 5 speed | |
| Gas Type | | NG (LP w/kit) | NG (LP w/kit) | NG (LP w/kit) | NG (LP w/kit) | NG (LP w/kit) | |
| Gas Connection Size | inch | 1/2 | 1/2 | 1/2 | 1/2 | 1/2 | |
| Net Weight | lbs | 131 | 139 | 142 | 153.5 | 169 | |
| Gross Weight | lbs | 162 | 168 | 185.5 | 191 | 210 | |



Data provided by AHRI